



## Composantes des systèmes pour eau de ville traitée, lacs et rivières

Filtre pour toute la maison  
8 et 11 GPM

### **AWP xx B-V Desinfection system**



The **AWP 40B-V** (10") or **50B-V** (20") high-flow filter housing, with a heavy duty 3 piece design. The housing has 1" FNPT connections, making it ideal for whole home treatment of a house or cottage. It is made from food grade material and can handle pressures up to 100 psi (6.9 bar) and temperatures up to 38°C (100°F This model has a white opaque sump with a blue pressure release head design. Installation and cartridge change out is made easy with the AWPxxB-V as it comes standard with a drain plug as well as mounting brackets and wrench.

8 GPM ( include 1x 10" sediment filter & 1x 20 " Taste , odors , chlorine & leads removal

+ a **UV SxQ-Pa** that provides point-of-use disinfection with a dose of 40 mJ/cm<sup>2</sup> at maximum flow rate system.

### Cartouches de remplacements

Enlèvement des Sédiments	CMB 510 HF (10") CMB 520 HF (20")
Enlèvement des goûts, odeurs, Chlore et métaux	C2-01 (10") C2-02 (20")

### **CMB-510-HF**



The **CMB-510-HF** is a 20 to 5 micron dirt/rust cartridge, with the 20 micron layer on the outside of the filter. This dual gradient density filter is grooved providing an increased surface area for improved filtering. It is constructed of 100% melt-blown high purity polypropylene (surfactant free, binder free, formaldehyde free and adhesive free) assisting in an improved dirt holding capacity, which is up to three times the capacity of conventional high flow filters. The CMB-510-HF has low pressure drops, a maximum operating temperature of <math><80^{\circ}\text{C}</math> (176°F) and has a 4 3/8" diameter (OD) with a length of 10".

### **CMB-520-HF**



The **CMB-520-HF** is a 20 to 5 micron dirt/rust cartridge, with the 20 micron layer on the outside of the filter. This dual gradient density filter is grooved providing an increased surface area for improved filtering. It is constructed of 100% melt-blown high purity polypropylene (surfactant free, binder free, formaldehyde free and adhesive free) assisting in an improved dirt holding capacity, which is up to three times the capacity of conventional high flow filters. The CMB-520-HF has low pressure drops, a maximum operating temperature of <math><80^{\circ}\text{C}</math> (176°F) and has a 4 3/8" diameter (OD) with a length of 20".

## C2-01



The **C2-01** is a modified block carbon cartridge with effective taste and odour reduction as well as exceptional dirt holding capacities. This cartridge has 10 micron filtration rating using a 100% coconut shell carbon, however there is no release of carbon fines. The C2-01 can be run at a **4.5 USGPM** flow rate for 22000 gallons, with a 5 psi pressure drop. It measures 4 ¼" in diameter and 9 ¾" in length. This cartridge will fit 10" big blue style housings!



## C2-02

The **C2-02** is a modified block carbon cartridge with effective taste and odour reduction as well as exceptional dirt holding capacities. This cartridge has 10 micron filtration rating using a 100% coconut shell carbon, however there is no release of carbon fines. The C2-02 can be run at a **7 USGPM** flow rate for 40000 gallons, with a 4.5 psi pressure drop. It measures 4 ¼" in diameter and 20" in length. This cartridge will fit 20" big blue style housings!